

JRM:dk



5,822,436

COF C

PATENT

UP
#34

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

Geoffrey B. Rhoads

Art Unit: 3642

Application No: 08/637,531

Patent No. 5,822,436

Filed: April 25, 1996

Issued October 13, 1998

For: PHOTOPGRAPHIC PRODUCTS AND
METHODS EMPLOYING EMBEDDED
INORMATION

Examiner: S. Cangialosi

CERTIFICATE

JUL 25 2001

Review
11/8/01

TO THE ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231

DEPARTMENT OF COMMERCE

LETTER

In checking the subject original Letters Patent with our copy of the application, the following errors which occurred in the printing of the patent were noted:

In the Specification

Column 1, Line 8, "August 9.,1995" should be --August 9, 1995,--

Column 2, Lines 10-13, delete "While the foregoing summary particularly addressed image data and photo-duplication equipment, the same principles are equally applicable to other types of steganographically-encoded data and other contexts." (See substitute specification and Amendment dated 11/13/1997.)

Column 8, line 14, after "rms noise as" insert --we did in the normal gain setting, we now find--.

Column 9, line 33, change "If S possible," to --If possible--.

Column 15, line 4, change "bow" to --how--.

Column 15, line 31, change "Printinig" to --printing--.

Column 19, line 53, change "'0". or a" to --"0" or a"--.

Column 30, line 52, change "P_{pcn}" to --P_{s-pcn}--.

Column 35, line 23, change "invention. hopefully" to --invention, hopefully--.

Column 37, line 38, change "JPEG/IMPEG" to --JPEG/MPEG--.

Column 46, line 34, change "thes e" to --these--.

Column 66, line 32, change "riciculous" to --ridiculous--.

Column 66, line 36, change "--2,400,000" to --~2,400,000—

Column 74, line 4, change "such AS" to --such as—

Column 76, line 58, insert the following: (See Amendment filed November 13, 1997.)

-- Errata

Applicant is preparing a steganographic marking/decoding "plug-in" for use with Adobe Photoshop software. The latest version of this software, presented as commented source code, is attached as Appendix B. The code was written for compilation with Microsoft's Visual C++ compiler, version 4.0, and can be understood by those skilled in the art.

This source code embodies several improvements to the technology disclosed in applicant's prior applications, both in encoding and decoding, and also in user interface.

Applicant's copyrights in the Exhibit B code are reserved, save for permission to reproduce same as part of the specification of the patent.

While the Exhibit B software is particularly designed for the steganographic encoding and decoding of auxiliary data in/from two-dimensional image data, many principles thereof are applicable to the encoding of digitized audio, as contemplated by the presently claimed invention.

Before concluding, it may be instructive to review some of the other fields where principles of applicant's technology (both in this application, and prior applications) can be employed.

One is document security for passports, visas, "green cards," etc. The photos on such documents can be processed to embed a subliminal data signal therein, serving to authenticate the document.

Related to the foregoing are objects (e.g. photos and ID cards) having biometric data embedded therein. One example of such biometric data is a fingerprint, allowing the authenticity of a person bearing such an ID to be checked.

Another application is smart business cards, wherein a business card is provided with a photograph having unobtrusive, machine-readable contact data embedded therein. (The same function can be achieved by changing the surface microtopology of the card to embed the data therein.)

Yet another promising application is in content regulation. Television signals, images on the internet, and other content sources (audio, image, video, etc.) can have data indicating their

"appropriateness" (i.e. their rating for sex, violence, suitability for children, etc.) actually embedded in the content itself rather than externally associated therewith. Television receivers, web browsers, etc., can discern such appropriateness ratings (e.g. by use of universal code decoding) and can take appropriate action (e.g. not permitting viewing of an image or video, or play-back of an audio source).

Credit cards are also likely candidates for enhancement by use of steganographic marking, providing an invisible and covert data carrier to extend functionality and improve security.

The field of merchandise marking is generally well served by familiar bar codes and universal product codes. However, in certain applications, such bar codes are undesirable (e.g. for aesthetic considerations, or where security is a concern). In such applications, applicant's technology may be used to mark merchandise, either through in innocuous carrier (e.g. a photograph associated with the product), or by encoding the microtopology of the merchandise's surface, or a label thereon.

There are applications -- too numerous to detail -- in which steganography can advantageously be combined with encryption and/or digital signature technology to provide enhanced security.

Medical records appear to be an area in which authentication is important. Steganographic principles -- applied either to film-based records or to the microtopology of documents -- can be employed to provide some protection against tampering.

Many industries, e.g. automobile and airline, rely on tags to mark critical parts. Such tags, however, are easily removed, and can often be counterfeited. In applications wherein better security is desired, industrial parts can be steganographically marked to provide an inconspicuous identification/authentication tag.

In various of the applications reviewed above and in applicant's earlier applications, different messages can be steganographically conveyed by different regions of an image (e.g. different regions of an image can provide different internet URLs, or different regions of a photocollage can identify different photographers). Likewise with other media (e.g. sound).

Some software visionaries look to the data when data blobs will roam the datawaves and interact with other data blobs. In such era, it will be necessary that such blobs have robust and incorruptible ways to identify themselves. Steganographic techniques again hold much promise here.

Finally, message changing codes -- recursive systems in which steganographically encoded messages actually change underlying steganographic code patterns -- offer new levels of sophistication and security. Such message changing codes are particularly well suited to applications such as plastic cash cards where time-changing elements are important to enhance security.

Again, while applicant prefers the particular forms of steganographic encoding, the foregoing applications (and applications disclosed in applicant's prior applications) can be practiced with other steganographic marking techniques.

Having described and illustrated the principles of my invention with reference to various embodiments thereof, it should be apparent that the invention can be modified in arrangement and detail without departing from such principles. Moreover, a variety of enhancements can be incorporated from the teachings of my prior applications.

Accordingly, I claim as my invention all such embodiments as come within the scope and spirit of the following claims and equivalents thereto.--

Appendix

Add Appendix B, omitted in the printed patent, but submitted to the Patent Office with the patent application.

All of the above errors are attributable to the Patent Office, and a Certificate of Correction is enclosed in duplicate to make formal notice of the errors in the subject patent.

Respectfully submitted,

DIGIMARC CORPORATION



23735

PATENT TRADEMARK OFFICE

Telephone: 503-885-9699

FAX: 503-885-9880

By

Joel R. Meyer
Registration No. 37,677

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 5,822,436
DATED : October 13, 1998
INVENTOR(S) : Geoffrey B. Rhoads

Page 1 of 64

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 1,

Line 8, "August 9,, 1995" should be -- August 9, 1995, --

Column 2,

Lines 10-13, delete "While the foregoing summary particularly addressed image data and photo-duplication equipment, the same principles are equally applicable to other types of steganographically-encoded data and other contexts."

Column 8,

Line 14, after "rms noise as" insert -- we did in the normal gain setting, we now find --.

Column 9,

Line 33, change "If S possible," to -- If possible --.

Column 15,

Line 4, change "bow" to -- how --.

Line 31, change "Printinig" to -- Printing --.

Column 19,

Line 53, change "'0". or a" to -- "0" or a" --.

Column 30,

Line 39, change " P_{pcn} " to -- P_{s-pcn} --.

Column 35,

Line 23, change "invention. hopefully" to -- invention, hopefully --.

Column 37,

Line 38, change "JPEG/IMPEG" to -- JPEG/MPEG --.

Column 46,

Line 34, change "thes e" to -- these --.

Column 66,

Line 32, change "riciculous" to -- ridiculous --.

Line 36, change "-2,400,000" to -- ~2,400,000 --.

Column 74,

Line 4, change "such AS" to -- such as --.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 5,822,436
DATED : October 13, 1998
INVENTOR(S) : Geoffrey B. Rhoads

Page 2 of 64

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 76,

Line 58, insert the following:

-- Errata

Applicant is preparing a steganographic marking/decoding "plug-in" for use with Adobe Photoshop software. The latest version of this software, presented as commented source code, is attached as Appendix B. The code was written for compilation with Microsoft's Visual C++ compiler, version 4.0, and can be understood by those skilled in the art.

This source code embodies several improvements to the technology disclosed in applicant's prior applications, both in encoding and decoding, and also in user interface.

Applicant's copyrights in the Exhibit B code are reserved, save for permission to reproduce same as part of the specification of the patent.

While the Exhibit B software is particularly designed for the steganographic encoding and decoding of auxiliary data in/from two-dimensional image data, many principles thereof are applicable to the encoding of digitized audio, as contemplated by the presently claimed invention.

Before concluding, it may be instructive to review some of the other fields where principles of applicant's technology (both in this application, and prior applications) can be employed.

One is document security for passports, visas, "green cards," etc. The photos on such documents can be processed to embed a subliminal data signal therein, serving to authenticate the document.

Related to the foregoing are objects (e.g. photos and ID cards) having biometric data embedded therein. One example of such biometric data is a fingerprint, allowing the authenticity of a person bearing such an ID to be checked.

Another application is smart business cards, wherein a business card is provided with a photograph having unobtrusive, machine-readable contact data embedded therein. (The same function can be achieved by changing the surface microtopology of the card to embed the data therein.)

Yet another promising application is in content regulation. Television signals, images on the internet, and other content sources (audio, image, video, etc.) can have data indicating their "appropriateness" (i.e. their rating for sex, violence, suitability for children, etc.) actually embedded in the content itself rather than externally associated therewith. Television receivers, web browsers, etc., can discern such appropriateness ratings (e.g. by use of universal code decoding) and can take appropriate action (e.g. not permitting viewing of an image or video, or play-back of an audio source).

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 5,822,436
DATED : October 13, 1998
INVENTOR(S) : Geoffrey B. Rhoads

Page 3 of 64

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Credit cards are also likely candidates for enhancement by use of steganographic marking, providing an invisible and covert data carrier to extend functionality and improve security.

The field of merchandise marking is generally well served by familiar bar codes and universal product codes. However, in certain applications, such bar codes are undesirable (e.g. for aesthetic considerations, or where security is a concern). In such applications, applicant's technology may be used to mark merchandise, either through in innocuous carrier (e.g. a photograph associated with the product), or by encoding the microtopology of the merchandise's surface, or a label thereon.

There are applications -- too numerous to detail -- in which steganography can advantageously be combined with encryption and/or digital signature technology to provide enhanced security.

Medical records appear to be an area in which authentication is important. Steganographic principles -- applied either to film-based records or to the microtopology of documents -- can be employed to provide some protection against tampering.

Many industries, e.g. automobile and airline, rely on tags to mark critical parts. Such tags, however, are easily removed, and can often be counterfeited. In applications wherein better security is desired, industrial parts can be steganographically marked to provide an inconspicuous identification/authentication tag.

In various of the applications reviewed above and in applicant's earlier applications, different messages can be steganographically conveyed by different regions of an image (e.g. different regions of an image can provide different internet URLs, or different regions of a photocollage can identify different photographers). Likewise with other media (e.g. sound).

Some software visionaries look to the data when data blobs will roam the datawaves and interact with other data blobs. In such era, it will be necessary that such blobs have robust and incorruptible ways to identify themselves. Steganographic techniques again hold much promise here.

Finally, message changing codes -- recursive systems in which steganographically encoded messages actually change underlying steganographic code patterns -- offer new levels of sophistication and security. Such message changing codes are particularly well suited to applications such as plastic cash cards where time-changing elements are important to enhance security.

Again, while applicant prefers the particular forms of steganographic encoding, disclosed in his prior Application the foregoing applications (and applications disclosed in applicant's prior applications) can be practiced with other steganographic marking techniques.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 5,822,436
DATED : October 13, 1998
INVENTOR(S) : Geoffrey B. Rhoads

Page 4 of 64

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Having described and illustrated the principles of my invention with reference to various embodiments thereof, it should be apparent that the invention can be modified in arrangement and detail without departing from such principles. Moreover, a variety of enhancements can be incorporated from the teachings of my prior applications.

Accordingly, I claim as my invention all such embodiments as come within the scope and spirit of the following claims and equivalents thereto. --

Appendix

Add Appendix B, as attached:

Signed and Sealed this

Second Day of April, 2002

Attest:

A handwritten signature in black ink, appearing to read "James E. Rogan", written over a horizontal line.

Attesting Officer

JAMES E. ROGAN
Director of the United States Patent and Trademark Office

APPENDIX B

```

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040

```

[illegible]

[illegible]

3

[illegible]

```

    *point = (float) { (1.0 - frac) * (double)(pin++) };
    *point++ = (float) { frac * (double)(pin++) };
    return scale_increment_id;
}

int get_id(
    float *real1,
    float *imaginary1,
    float *real2,
    float *imaginary2,
    int bits,
    float offset)
{
    int i, highest;
    float *preal1, *preal2, *pimaginary1, *pimaginary2;
    float mag1, mag2, dot, dot2, cross, median1, highest_ratio, temp;
    /* calculate phase differences and related then into real and imaginary */
    for (i = 0; i < bits; i++) {
        preal1 = real1 + i * 2;
        preal2 = real2 + i * 2;
        pimaginary1 = imaginary1 + i * 2;
        pimaginary2 = imaginary2 + i * 2;
        mag1 = (float)sqrt((double)(preal1 * preal1 + pimaginary1 * pimaginary1));
        mag2 = (float)sqrt((double)(preal2 * preal2 + pimaginary2 * pimaginary2));
        dot = (preal1 * preal2 + pimaginary1 * pimaginary2) / (mag1 * mag2);
        dot2 = (float)sqrt((double)(dot * dot));
        if (mag1 > mag2) {
            cross = (float)(dot * mag2 - (float)0.0);
            else cross = (float)0.0;
        } else {
            cross = (float)(dot * mag1 - (float)0.0);
        }
        dot = dot2 * mag2;
        *preal1++ = dot;
        *pimaginary1++ = cross;
    }
    /* search for highest value, then median find the center */
    preal1 = real1;
    pimaginary1 = imaginary1;
    for (i = 0; i < bits; i++) {
        if (highest < *preal1)
            highest = *preal1;
        if (highest < *pimaginary1)
            highest = *pimaginary1;
        preal1++;
        pimaginary1++;
    }
    if (highest < 0) {
        median1 = (float)(highest - 1);
        median2 = (float)(highest - 1);
        median3 = (float)(highest - 1);
    } else {
        median1 = (float)(highest - 1);
        median2 = (float)(highest - 1);
        median3 = (float)(highest - 1);
    }
    median1 = (float)(median1 - 1);
    median2 = (float)(median2 - 1);
    median3 = (float)(median3 - 1);
    ratio = get_median_float(median1, median2, median3);
    offset = (float)highest * ratio;
    if (offset > (float)(bits/2.0)) offset -= (float)bits;
    return(i);
}

int write_out(
    int template_id,
    int template_dim,
    int suspect_dim,
    int suspect_char,
    int suspect_ydim,
    float *suspect_ydim,
    int which)
{
    int i, j;
    float *pwindow;
    convert_to_amplitude(ftemp, in_dim);
    if (window_id == 0) {
        float *window_function = new float[suspect_dim];
        point = out;
        for (i = 0; i < suspect_dim; i++) {
            for (j = 0; j < pwindow; j++) {
                *point++ = *pwindow;
            }
        }
        delete [] window_function;
    }
    return(i);
}

int get_best_candidate(
    float *ftemp,
    int bits,
    float in_dim,
    int xdim,
    int ydim,
    int xdim_orig,
    int ydim_orig,
    float *rotation,
    float *scale,
    float *x_trans,
    float *y_trans,
    float *template_real)
{
    int i, highest;
    float highest = -(float)120;
    for (i = 0; i < number_candidates; i++) {
        for (j = 0; j < bits; j++) {
            rotate_scale_translate_image(ftemp, dim, in_dim, ydim, xdim_orig, ydim_orig,
                result_id, in_dim, bits, 1, xtrans, ytrans, scale, 1);
            get(template_real, ftemp, dim, bits, 1, xtrans, ytrans, scale, 1);
            if (highest < highest_value)
                highest = highest_value;
            x_trans[i] = xtrans;
            y_trans[i] = ytrans;
        }
    }
    rotation[0] = rotation(highest - 1);
    scale[0] = scale(highest - 1);
    x_trans[0] = xtrans(highest - 1);
    y_trans[0] = ytrans(highest - 1);
    return(i);
}

double log_id_rmap(
    float *in,
    float *out,
    int dim)
{
    int i, dim2 = dim/2;
    float *pin, *pout;
    double scale_increment_id;
    scale_increment_id = pow(1.0 / (double)START_RADIUS_ID, 1.0 / (double)dim);
    point = out;
    for (i = 0; i < dim; i++) {
        *point++ = (double)START_RADIUS_ID * pow(scale_increment_id, (double)i);
        *point++ = (double)radius * (double)xx;
        pin = in;
    }
}

```


[illegible]

```

// while (foo) {
//     x = x + 1; // x is the optimal pair
//     refine_axis(template, template_xdim, template_ydim, suspect, suspect_xdim,
//     suspect_ydim, 0, 0, optimal_pair);
//     refine_axis(template, template_xdim, template_ydim, suspect, suspect_xdim,
//     suspect_ydim, 1, 1, optimal_pair);
//     refinement = refined_rotation(y, suspect, suspect_xdim, suspect_ydim, template,
//     suspect_xdim, suspect_ydim, 0, 0, optimal_pair);
//     // now we have a rotation, we can use it to refine the template
//     rotation = refinement;
// }
// alignment.refinement = refinement;
// return(1);
}

// subroutine for direct registration
int get_center_and_center(
    float *x,
    float *y,
    float *x_trans,
    float *y_trans,
    int ydim,
    int xdim,
    int downsamples)
{
    float a_const, b_const;
    // the center of the suspect array should translate to...
    // (template_xdim - 1)/2, (template_ydim - 1)/2, same on y??
    // note that the origin of the downsampled arrays actually is
    // positioned at (downsample-1)/2, (downsample-1)/2 in the coordinates of the
    // original array
    float downsamples;
    x_trans = (float)downsamples;
    y_trans = (float)downsamples;
    x[4] = (float)((float)downsamples - 1)/(float)2.0 * x_trans;
    y[4] = (float)((float)downsamples - 1)/(float)2.0 * y_trans;
    a_const = (float)cos((double)rotation*(M_PI/180.0)/scale);
    b_const = (float)sin((double)rotation*(M_PI/180.0)/scale);
    x[0] = x[4] + (a_const*(float)xdim-1) + b_const*(float)ydim-1)/(float)2.0;
    y[0] = y[4] + (b_const*(float)xdim-1) + a_const*(float)ydim-1)/(float)2.0;
    x[1] = x[4] + (a_const*(float)xdim-1) + b_const*(float)ydim-1)/(float)2.0;
    y[1] = y[4] + (b_const*(float)xdim-1) + a_const*(float)ydim-1)/(float)2.0;
    x[2] = x[4] + (a_const*(float)xdim-1) + b_const*(float)ydim-1)/(float)2.0;
    y[2] = y[4] + (b_const*(float)xdim-1) + a_const*(float)ydim-1)/(float)2.0;
    x[3] = x[4] + (a_const*(float)xdim-1) + b_const*(float)ydim-1)/(float)2.0;
    y[3] = y[4] + (b_const*(float)xdim-1) + a_const*(float)ydim-1)/(float)2.0;
    return(1);
}

int final_image(
    int *x, // x is the optimal pair
    int *y, // y is the optimal pair
    int *x_trans,
    int *y_trans,
    int *xdim,
    int *ydim,
    int *y,
    int *x,
    int *num_channels,
    int *option)
{
    unsigned char *out;
    int i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z;
    float xdim_x, ydim_y, xdim_x_trans, ydim_y_trans, xdim_x_dist,
    float xdim_y_trans, xdim_x_trans, xdim_y, xdim_x, xdim_y_dist;
    unsigned char *in;
    if (option == 1) // clear template array
    {
        for (i=0; i<(num_channels*xdim*xdim); i++) *(out+i) = (unsigned char)0;
    }
}

```


[illegible]

[illegible]

[illegible]


```

    decUsed = ((LSPITVALINFOHEADER)lpdi)->decUsed;
    if (decUsed == 0)
        return (WORD)decUsed;
    }

    /* Calculate the number of colors in the color table based on
     * the number of bits per pixel for the DIB.
     */
    if ((IS_WINDO_DIB(lpdi))
        else *bitCount = ((LSPITVALINFOHEADER)lpdi)->bitCount;
        else *bitCount = ((LSPITVALINFOHEADER)lpdi)->bitCount;
        /* return number of colors based on bits per pixel */
        switch (*bitCount)
        {
            case 1:
                return 2;
            case 4:
                return 16;
            case 8:
                return 256;
            default:
                return 0;
        }
    }

    /*.....*/
    *bitCount();
    *Parameter;
    *LSPTR lpdi - pointer to packed-DIB memory block
    *Return Value:
    *WORD - number of bits per pixel
    *Description:
    *Added by CLV Davidson 11/7/95. Simply returns the number of bits per
    * pixel (1, 4, 8, 24), regardless of the state of the color table.
    *.....*/
    WORD *bitCount;
    if ((IS_WINDO_DIB(lpdi))
        else *bitCount = ((LSPITVALINFOHEADER)lpdi)->bitCount;
        else *bitCount = ((LSPITVALINFOHEADER)lpdi)->bitCount;
    }
    return *bitCount;
    /*.....*/
    /* Clipboard support
    /*.....*/

    Function: CopyHandle (from DIB DIBVIEW sample clipboard.c)
    Purpose: Makes a copy of the given global memory block. Returns
             a handle to the new memory block (NULL on error).
    Routine stolen verbatim out of SHOOBIB.
    Param: h - handle to global memory to duplicate.
    Returns: Handle to new global memory block.

    HANDLE WINAPI CopyHandle (HANDLE h)
    {
        HGLOBAL hCopy;
        if (h == NULL)
            return NULL;
        return hCopy;
    }
}

```


[illegible]

[illegible]

[illegible]

```

// MakePackedData()
// This function copies the DIB image data into a packed format. This
// is important for two reasons. 1) The DIB formatted data is arranged
// so that each scan line starts on a long word boundary, which means
// that the data is not aligned for efficient access. 2) The DIB data
// is 32 bits wide, but the image data is only 24 bits wide. This
// means that the data is padded with zeros. This function copies
// the data to the core algorithm. Also, 3) If a palette is used, it
// is copied into the packed data. The packed data is then used
// to create the image. The packed data is then used to create the
// image. The packed data is then used to create the image.
// WARNING: CURRENT IMPLEMENTATION ASSUMES 3 BIT GRAY-SCALE IMAGE DATA.
// void Image::MakePackedData(void)
{
    unsigned char *hpdata;
    int line_cnt, line, i;
    BOOLEAN bottom_up;

    // Create space and get handle for the packed data of the image.
    m_hpackeddata = (GLOBALLOCK(m_hDIB) + (long) m_nWidth);
    if (m_hpackeddata == 0)
        AfxThrowMemoryException();

    // Lock the packed data global memory (leave locked until destructor).
    m_hpackeddata = (unsigned char *)GlobalLock((HANDLE) m_hpackeddata);

    hpdata = m_hpackeddata;

    // Images may be top to bottom or bottom to top.
    if (m_lpHeader->biHeight > 0)
    {
        bottom_up = TRUE;
        line = m_nDib - 1;
    }
    else
    {
        bottom_up = FALSE;
        line = 0;
    }

    // TEST CODE
    // For Geoff, don't let it correct for bottom_up
    line = 0;

    for (line_cnt = 0; line_cnt < m_nDib; line_cnt++)
    {
        // Set pointer to first byte for this scan line.
        hpdata = m_hpackeddata + (long) m_nWidth * line;
        for (i = 0; i < m_nDib; i++)
        {
            *hpdata++ = *hpdata++;
        }
        if (bottom_up) line--;
        else line++;
    }

    // Next, we force the palette to be our standard 8 bit gray-scale
    // palette.
    if (m_nBitDepth == 0)
    {
        // Set per to beginning of palette
        LPDWORD pal = m_hpalette;
        for (i = 0; i < 256; i++)
        {
            pal(i).rgbBlue = pal(i).rgbGreen = pal(i).rgbRed = i;
        }
    }
    else
    {
        m_hpalette = NULL; // Can only support 8 bit image data. NULL.
        m_nColorTableEntries = 0;
    }

    // Now go through each line and create the packed array.
    for (line_cnt = 0; line_cnt < m_nDib; line_cnt++)
    {
        // Set pointer to first byte for this scan line.
        hpdata = m_hpackeddata + (long) m_nWidth * line;
        for (i = 0; i < m_nDib; i++)
        {
            if (m_nBitDepth == 24)
            {
                *hpdata++ = *hpdata++;
            }
            else
            {
                // For 8 bit (and any other non 24 bit data) we
                // take the image data to be indices into the color
                // table. We look up the actual value. Note we
                // assume gray-scale (i.e., r/g/b triples are all equal).
                *hpdata++ = m_lpColorTable(hpdata(i)).rgbGreen;
            }
        }
        if (bottom_up) line--;
        else line++;
    }

    // UnpackData()
    // This function moves the contents of the packed data array back into
    // the DIB data space. This would be used, for example, after one the
    // core algorithm has been run. It would be used to update the DIB
    // requires that we create our own palette, since otherwise we don't know
    // that the new data values have corresponding entries in the palette.
    // WARNING: CURRENT IMPLEMENTATION ASSUMES 3 BIT GRAY-SCALE IMAGE DATA.
    // void Image::UnpackData(void)
    {
        unsigned char *hpdata;
    }

```

```

    unsigned char *hpdata;
    int line_cnt, line, i;
    BOOLEAN bottom_up;

    // Images may be top to bottom or bottom to top.
    if (m_lpHeader->biHeight > 0)
    {
        bottom_up = TRUE;
        line = m_nDib - 1;
    }
    else
    {
        bottom_up = FALSE;
        line = 0;
    }

    // TEST CODE
    // For Geoff, don't let it correct for bottom_up
    line = 0;

    for (line_cnt = 0; line_cnt < m_nDib; line_cnt++)
    {
        // Set pointer to first byte for this scan line.
        hpdata = m_hpackeddata + (long) m_nWidth * line;
        for (i = 0; i < m_nDib; i++)
        {
            *hpdata++ = *hpdata++;
        }
        if (bottom_up) line--;
        else line++;
    }

    // Next, we force the palette to be our standard 8 bit gray-scale
    // palette.
    if (m_nBitDepth == 0)
    {
        // Set per to beginning of palette
        LPDWORD pal = m_hpalette;
        for (i = 0; i < 256; i++)
        {
            pal(i).rgbBlue = pal(i).rgbGreen = pal(i).rgbRed = i;
        }
    }
    else
    {
        m_hpalette = NULL; // Can only support 8 bit image data. NULL.
        m_nColorTableEntries = 0;
    }

    // Now go through each line and create the packed array.
    for (line_cnt = 0; line_cnt < m_nDib; line_cnt++)
    {
        // Set pointer to first byte for this scan line.
        hpdata = m_hpackeddata + (long) m_nWidth * line;
        for (i = 0; i < m_nDib; i++)
        {
            if (m_nBitDepth == 24)
            {
                *hpdata++ = *hpdata++;
            }
            else
            {
                // For 8 bit (and any other non 24 bit data) we
                // take the image data to be indices into the color
                // table. We look up the actual value. Note we
                // assume gray-scale (i.e., r/g/b triples are all equal).
                *hpdata++ = m_lpColorTable(hpdata(i)).rgbGreen;
            }
        }
        if (bottom_up) line--;
        else line++;
    }

    // UnpackData()
    // This function moves the contents of the packed data array back into
    // the DIB data space. This would be used, for example, after one the
    // core algorithm has been run. It would be used to update the DIB
    // requires that we create our own palette, since otherwise we don't know
    // that the new data values have corresponding entries in the palette.
    // WARNING: CURRENT IMPLEMENTATION ASSUMES 3 BIT GRAY-SCALE IMAGE DATA.
    // void Image::UnpackData(void)
    {
        unsigned char *hpdata;
    }

```

[illegible]

```

{
    // For a bit (and any other non 24 bit data) we
    // take the image data to be indices into the color
    // table. We look up the actual color values from
    // the table. (i.e., eight tuples are all equal -
    // we read the green.
    *pData++ = *pBitmapColors[pLine(i)].rgbgreen;

}
if (bottom_up) line++;
else line--;

}
// End of function
// =====
// This function saves the contents of the packed data array back into
// the DIS data space. This would be used, for example, after one the
// core algorithms have been used to sign the data in the packet. This
// requires that we create our own palette, since otherwise we don't know
// that the new data values have corresponding entries in the palette.
// WARNING: CURRENT IMPLEMENTATION ASSUMES A BIT GRAY-SCALE IMAGE DATA
// ON 34 BIT COLOR IMAGE DATA
void Image::ImpDataToVoid()
{
    unsigned char *pLine;
    unsigned char *pSignedChar;
    int line_cnt, line, i, j;
    BOOLEAN bottom_up;

    bottom_up = FALSE;
    line = 0;
    while (line < m_nHeight)
    {
        // TEST CODE
        // For Geoff, don't let it correct for bottom_up
        // line = 0;
        // line = m_nHeight;
        // line = 0;
        // line = m_nHeight - 1;
        // else
        {
            bottom_up = FALSE;
            line = 0;
        }
        for (line_cnt = 0; line_cnt < m_nWidth; line_cnt++)
        {
            // We pointers to first byte for this scan line.
            // We use m_nHeightLine - 1 long! m_nHeightLine;
            for (i = 0, j = 0; i < m_nWidth; i++)
            {
                if (m_BitsPerPixel == 24)
                {
                    // red
                    pLine[(i*3) + 0] = *pData++;
                    // green
                    pLine[(i*3) + 1] = *pData++;
                    // blue
                    pLine[(i*3) + 2] = *pData++;
                }
                else
                {
                    pLine[(i*3) + 0] = *pData++;
                }
            }
            if (bottom_up) line--;
            else line++;
        }
        // Next, we force the palette to be our standard 4 bit gray-scale
        // palette.
        if (m_BitsPerPixel == 8)
        {
            // Set ptr to beginning of palette
            unsigned pal = m_nBitmapColors;
            for (i = 0, j = 256; i++)
            {
                pal[i].rgbgreen = pal[i].rgbgreen = 1;
            }
        }
        else if (m_BitsPerPixel == 24)
        {
            // Don't do any palette work for 24 bit color. There is no palette.
        }
    }
}

```

[illegible]

[illegible]

[illegible]


```

// CONSTRUCTOR FOR SIGHAR FILLING OBJECT WHICH
// TAKES THE COMMAND LINE STRING AS AN ARGUMENT
// AND RETURNS A MESSAGE TO BE USED IN THE
// SIGHAR FILLING FUNCTION.

signatureParam::signatureParam(LSSTR cmd_line) // Constructor based on command line
{
    char *dash_ptr = "cmd_type", *cmd; // commands;
    const char *dash_ptr2 = "-msg_ptr";

    parameters.input_filenames = NULL;
    parameters.output_filenames = NULL;
    parameters.registry_name = NULL;
    parameters.user_key = 1;
    parameters.gain = (float) 100.0;
    parameters.gamma = (float) 0.07;
    parameters.bump_size = 1;
    parameters.lut_scale = (float) 100.0;
    parameters.super_reader_flag = FALSE;
    parameters.msg_ptr = (const char *) DeMessage();
    TRACE("Debug in signatureParam constructor. Message is: %s\n", dbg_msg_ptr);
    // Make a copy of the command line that we can mutilate
    commands = new char[strlen(cmd_line) + 1];
    strcpy(commands, cmd_line);
    dash_ptr = NULL;

    // If the command line doesn't start w/ a '-', then the command line is
    // invalid argument; the filenames This case comes up when the program
    // is invoked by dropping a filename onto the executable in Win95 explorer.
    {
        if (strlen(cmd_line) > 0 && cmd_line[0] != '-')
        {
            parameters.input_filenames = new char[strlen(cmd_line) + 1];
            strcpy(parameters.input_filenames, cmd_line);
        }
    }
    // Otherwise, we check for the multiple argument format of the command line,
    // in which arguments pairs are used, e.g., "%f %f -filenames".
    {
        do
        {
            // Find the last '-' character
            dash_ptr = strrchr(cmd_line, '-');
            if (dash_ptr != NULL)
            {
                cmd_type = dash_ptr + 1;
                cmd = cmd_type + 1;

                // Create an in-core input stream
                istreamstream(cmd, strlen(cmd));
                switch (cmd_type)
                {
                    case '%f':
                        istreamstream >> parameters.gain;
                        break;
                    case '%F':
                        istreamstream >> parameters.gamma;
                        break;
                    case '%f%F':
                        istreamstream >> parameters.gamma;
                        break;
                    case '%f':
                        istreamstream >> parameters.lut_scale;
                        break;
                    case '%F':
                        istreamstream >> parameters.bump_size;
                        break;
                    case '%f%F':
                        istreamstream >> parameters.gamma;
                        default:
                            parameters.message = cmd;
                            break;
                }
            }
            // parameters.message = new char(strlen(cmd) + 1);
            // istreamstream >> parameters.message;
            // istreamstream >> parameters.input_filenames;
            // parameters.message = cmd;
            case '%f':
                istreamstream >> parameters.gain;
                break;
            case '%F':
                istreamstream >> parameters.gamma;
                break;
            case '%f%F':
                istreamstream >> parameters.gamma;
                default:
                    parameters.message = cmd;
                    break;
            }
        } while (dash_ptr != NULL);
    }
}

```

-27-

[illegible]

[illegible]

[illegible]

[illegible]

```

}

/* fill the message string based on bit_totals */
for(i=0; i<message_length; i++)
{
    message[i]=0;
}
else
{
    message[i]=0;
}
}

/* for i = 0; i < message_length; i++
{
    // normalizing by the magnitude, be sure we aren't
    // dividing by zero, but the magnitude is either
    // bit_mag[i] = (float)0;
    // bit_mag[i] = epsilon;

    bit_total[i] /= (float) sqrt( (double) bit_mag[i] );

}

/* Compute the "crude metric", an estimate of the spread of the
// bit level detector's results. The referenced array is either
// the original message, or the reference message, or the
// newly computed estimate of the message.

-metric = get_crude_metric(reference_message, bit_total, range, message_length);

delete [] data_float;
delete [] data_int;
delete [] bit_total;
delete [] key_value;
delete [] bit_mag;

return;
}

// float i;
// float *data;
// int *data_int;
// int *data_int;
// long x_offset, int number_channels;
// unsigned char *pdata;
// float *pdata;

pdata = data;
pdata_data_float;
if (number_channels == 1)
{
    for (i = 0; i < x_extent; i++)
    {
        *pdata++ = (float) *pdata++;
    }
    else if (number_channels == 2)
    {
        for (i = 0; i < x_extent; i++)
        {
            *pdata++ = (float) *pdata++;
            *pdata++ = (float) *pdata++;
        }
    }
}

// remove_pdata
// void remove_main(float *array, long length)
// {
//     long i;
//     float total = (float) 0.0;
//     for (i = 0; i < length; i++)
//     {
//         total += array[i];
//     }
//     total /= (float) length;
//     for (i = 0; i < length; i++)
//     {
//         array[i] -= total;
//     }
}

```

[illegible]


```

// remove low and/or high frequencies
// low pass filter would divide it row on. fftdim/2
int wco = 0;
if (wco) {
    int i;
    int kcount_low = 1;
    int kcount_high = 1;
    for (i = 0; i < fftdim/2; i++) {
        pimage = (float)0.0;
        for (j = 0; j < account; j++) {
            pimage += (fftdata - kcount);
        }
    }
}

// inverse fft
realfft2d_in_place(image, bits, 1, wco, w1);
for (liney_offset = liney_offset - y_extent; liney_offset < liney_offset + y_extent; liney_offset++) {
    // load key values
    // play = array((liney_offset) * key_alphabet, key_alphabet * key_alphabet);
    for (liney_offset = liney_offset - y_extent; liney_offset < liney_offset + y_extent; liney_offset++) {
        for (liney_offset = liney_offset - y_extent; liney_offset < liney_offset + y_extent; liney_offset++) {
            // fill the message string based on bit_total
            for (i = 0; i < message_length; i++) {
                // before normalizing by the magnitudes, be sure we aren't
                // dividing by zero (this happens for an image w/ zero energy.
                // if bit_total[i] == 0.0) {
                //     bit_mag[i] = 0.0;
                // } else {
                //     message[i] = 1;
                // }
            }
        }
    }

    // Compute the "energy metric", an estimate of the spread of the
    // bit level detector's results. The reference array is either
    // the known message (if it was available to caller) or the
    // newly computed estimate of the message.
    metric = get_true_metric(reference_array, bit_total, range, message_length);

    delete [] bit_total;
    delete [] bit_mag;
    delete [] key_value;
    delete [] image;
    delete [] w1;
    return;
}

// get_read_detail_vector()
// get_read_detail_vector()
// get_read_detail_vector()

```

[illegible]

[illegible]

```

//-----
// get_detail_vector()
//-----
int get_detail_vector(
    unsigned char *data, *ps1, *ps2,
    float *detail_vector,
    unsigned char *data,
    int xsize,
    int ysize,
    int total_rows,
    int total_cols,
    int number_channels)
{
    unsigned char *pdata, *ps1, *ps2;
    float *pdetail_vector, *pdetail_vector_detail;
    //-----
    // this function creates a "scaled" vector for the current scan line.
    // based on a crude metric of "local detail"
    if (number_channels == 1)
    {
        //-----
        // perform first and last elements outside loop so that an internal if statement is
        // avoided
        base = (int)(pdata+1);
        temp = abs(base - (int)(ps1+1));
        *pdetail_vector++ = detail jut(temp); // make sure it goes up to 1024 elements
        for (i=1; i<(total_cols-1); i++)
        {
            base = (int)(pdata+i);
            temp = abs(base - (int)(ps1+i));
            temp = abs(base - (int)(ps2+i));
            *pdetail_vector++ = detail jut(temp);
        }
        base = (int)(pdata+total_cols-1);
        temp = abs(base - (int)(ps1+total_cols-1));
        temp = abs(base - (int)(ps2+total_cols-1));
        *pdetail_vector++ = detail jut(temp); // make sure it goes up to 1024 elements
    }
    else if (number_channels == 3)
    {
        // use the green channel only just for speed's sake
        pdata = data+1;
        ps1 = data+1;
        ps2 = data+1;
        if (total_rows == 1)
        {
            // perform first and last elements outside loop so that an internal if statement is
            // avoided
            base = (int)(pdata+1);
            temp = abs(base - (int)(ps1+1));
            temp = abs(base - (int)(ps2+1));
            *pdetail_vector++ = detail jut(temp); // make sure it goes up to 1024 elements
            for (i=1; i<(total_cols-1); i++)
            {
                base = (int)(pdata+i);
                temp = abs(base - (int)(ps1+i));
                temp = abs(base - (int)(ps2+i));
                *pdetail_vector++ = detail jut(temp);
            }
            base = (int)(pdata+total_cols-1);
            temp = abs(base - (int)(ps1+total_cols-1));
            temp = abs(base - (int)(ps2+total_cols-1));
            *pdetail_vector++ = detail jut(temp); // make sure it goes up to 1024 elements
        }
        else
        {
            // perform first and last elements outside loop so that an internal if statement is
            // avoided
            base = (int)(pdata+1);
            temp = abs(base - (int)(ps1+1));
            temp = abs(base - (int)(ps2+1));
            *pdetail_vector++ = detail jut(temp); // make sure it goes up to 1024 elements
            for (i=1; i<(total_cols-1); i++)
            {
                base = (int)(pdata+i);
                temp = abs(base - (int)(ps1+i));
                temp = abs(base - (int)(ps2+i));
                *pdetail_vector++ = detail jut(temp);
            }
            base = (int)(pdata+total_cols-1);
            temp = abs(base - (int)(ps1+total_cols-1));
            temp = abs(base - (int)(ps2+total_cols-1));
            *pdetail_vector++ = detail jut(temp); // make sure it goes up to 1024 elements
        }
    }
    return(i);
}
//-----
// load_detail_jut()
//-----
// This function loads the scaling factor based on local detail
// int load_detail_jut( float *detail jut, float scale) // explicitly written for a bit
// int i, status=1;
// float length=(float)(DETAIL_STOP-DETAIL_START);

```


[illegible]

[illegible]

[illegible]

[illegible]

[illegible][illegible]

[illegible]

-44-

```
// (CMDVIEW)view()--saveViewType (new_type);
}

// We get here only if we failed to find a view of "old_type"
return NULL;

////////////////////////////////////
OnSettingAutoprint()
{
    When the user toggles the "Auto-print Report" item in
    the menu bar, this function will be called. It simply
    toggles the corresponding member variable.

    // Toggle the auto-print flag
    bool OnAutoPrint = !m_autoprint;

    if (m_autoprint == TRUE)
        m_autoprint = FALSE;
    else
        m_autoprint = TRUE;

    //////////////////////////////////////
    OnPostDataSettingAutoprint()

    The framework calls this function whenever it is about
    to post data to the printer. This function will set the
    report option based on our internal state variable
    m_autoprint. We set or clear the check mark next to
    the "Auto-Print" menu item accordingly.

    // Set or clear the check mark next to the menu
    // item
    if (m_autoprint == TRUE)
        pCmdUI->SetCheck(TRUE);
    else
        pCmdUI->SetCheck(FALSE);

    //////////////////////////////////////
    OnSettingReader()

    Invoked when the user selects the Ctrl+R-->Reader...
    menu option. Presents a hand-drawn dialog object, and
    deals with the operators inputs. On OK, the Read() function
    is called. On Cancel, the program returns to the temp-
    ation core algorithms to try to detect an embedded
    diagram message.

    // Check to see if we are in a legal state for reading.
    if (m_state == MD_IMAGE)
    {
        MessageBox(NULL,
            "An x or y bit image must be loaded before using the Reader.",
            MB_ICONINFORMATION | MB_OK);
        return;
    }

    // Determine the type of the active window
    viewType = GetActiveWindowType();

    // If active window is not acceptable for reading, warn user a return
    // from the menu option.
    if (viewType != SIGNED_VIEW ||
        viewType != ALIGNED_VIEW)
    {
        MessageBox(NULL,
            "The active window must contain an image to be read.",
            MB_ICONINFORMATION | MB_OK);
        return;
    }

    // Set pointer to the image which is to be read.
    m_image = GetImageFromWindow(
        GetActiveWindow());
}
```

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

```

MESSAGE by defining the macro CPG on the command line. For example:
MESSAGE /P "signerWin32.exe" CPG=signer - Win32 Debug"
MESSAGE
MESSAGE Possible choices for configuration are:
MESSAGE   signer - Win32 Release" (based on "Win32 (test) Application")
MESSAGE   signer - Win32 Debug" (based on "Win32 (test) Application")
MESSAGE
MESSAGE An invalid configuration is specified.
MESSAGE
ENDIF

IF "%OS%" == "Windows-NT"
    FULL=
    ELSE
        FULL=
    ENDIF
    IF "%CPG%" == "signer - Win32 Release"
        CPG=signerWin32.exe
    ELSE
        CPG=signerWin32.exe
    ENDIF
    IF "%CPG%" == "signer - Win32 Release"
        # PROP BASE Use_MTC 1
        # PROP BASE Use_Debug_Libraries 0
        # PROP BASE Target_Dir ""
        # PROP BASE Intermediate_Dir "Release"
        # PROP BASE Target_Dir ""
        # PROP Use_Debug_Libraries 0
        # PROP Use_Debug_Libraries 0
        # PROP Output_Dir "Release"
        # PROP Intermediate_Dir "Release"
        # PROP Target_Dir ""
        OUTDIR=Release
        ALL = $(OUTDIR)\signerWin32.exe" $(OUTDIR)\signerWin32.bsc"
        CLINK =
        CLINK = $(RELEASE)\signerWin32.bsc"
        -c $(RELEASE)\WinMain.cbr"
        -c $(RELEASE)\signerWin32.cbr"
        -c $(RELEASE)\Cuckoo.cbr"
        -c $(RELEASE)\Vrt.cbr"
        -c $(RELEASE)\StdAfx.cbr"
        -c $(RELEASE)\Packchng.cbr"
        -c $(RELEASE)\SignWin.cbr"
        -c $(RELEASE)\Temp.cbr"
        -c $(RELEASE)\Params.cbr"
        -c $(RELEASE)\Align.cbr"
        -c $(RELEASE)\Read.cbr"
        -c $(RELEASE)\Bundling.cbr"
        -c $(RELEASE)\SignWin32.exe"
        -c $(RELEASE)\Params.cbr"
        -c $(RELEASE)\Align.cbr"
        -c $(RELEASE)\Read.cbr"
        -c $(RELEASE)\Bundling.cbr"
        -c $(RELEASE)\SignWin32.exe"
        -c $(RELEASE)\Params.cbr"
        -c $(RELEASE)\Align.cbr"
        -c $(RELEASE)\Read.cbr"
        -c $(RELEASE)\Bundling.cbr"
        -c $(RELEASE)\SignWin32.cbr"
        -c $(RELEASE)\StdAfx.cbr"
        -c $(RELEASE)\Packchng.cbr"
        -c $(RELEASE)\SignWin32.cbr"
        -c $(RELEASE)\Params.cbr"
        -c $(RELEASE)\Temp.cbr"
        -c $(RELEASE)\SignWin32.cbr"
    ENDIF
    IF NOT exist "$(OUTDIR)\$(NULL)" mkdir "$(OUTDIR)"
    # ADD BASE /nologo /MT /O2 /O1 /O3 /O4 /O5 /O6 /O7 /O8 /O9 /O10 /O11 /O12 /O13 /O14 /O15 /O16 /O17 /O18 /O19 /O20 /O21 /O22 /O23 /O24 /O25 /O26 /O27 /O28 /O29 /O30 /O31 /O32 /O33 /O34 /O35 /O36 /O37 /O38 /O39 /O40 /O41 /O42 /O43 /O44 /O45 /O46 /O47 /O48 /O49 /O50 /O51 /O52 /O53 /O54 /O55 /O56 /O57 /O58 /O59 /O60 /O61 /O62 /O63 /O64 /O65 /O66 /O67 /O68 /O69 /O70 /O71 /O72 /O73 /O74 /O75 /O76 /O77 /O78 /O79 /O80 /O81 /O82 /O83 /O84 /O85 /O86 /O87 /O88 /O89 /O90 /O91 /O92 /O93 /O94 /O95 /O96 /O97 /O98 /O99 /O100 /O101 /O102 /O103 /O104 /O105 /O106 /O107 /O108 /O109 /O110 /O111 /O112 /O113 /O114 /O115 /O116 /O117 /O118 /O119 /O120 /O121 /O122 /O123 /O124 /O125 /O126 /O127 /O128 /O129 /O130 /O131 /O132 /O133 /O134 /O135 /O136 /O137 /O138 /O139 /O140 /O141 /O142 /O143 /O144 /O145 /O146 /O147 /O148 /O149 /O150 /O151 /O152 /O153 /O154 /O155 /O156 /O157 /O158 /O159 /O160 /O161 /O162 /O163 /O164 /O165 /O166 /O167 /O168 /O169 /O170 /O171 /O172 /O173 /O174 /O175 /O176 /O177 /O178 /O179 /O180 /O181 /O182 /O183 /O184 /O185 /O186 /O187 /O188 /O189 /O190 /O191 /O192 /O193 /O194 /O195 /O196 /O197 /O198 /O199 /O200 /O201 /O202 /O203 /O204 /O205 /O206 /O207 /O208 /O209 /O210 /O211 /O212 /O213 /O214 /O215 /O216 /O217 /O218 /O219 /O220 /O221 /O222 /O223 /O224 /O225 /O226 /O227 /O228 /O229 /O230 /O231 /O232 /O233 /O234 /O235 /O236 /O237 /O238 /O239 /O240 /O241 /O242 /O243 /O244 /O245 /O246 /O247 /O248 /O249 /O250 /O251 /O252 /O253 /O254 /O255 /O256 /O257 /O258 /O259 /O260 /O261 /O262 /O263 /O264 /O265 /O266 /O267 /O268 /O269 /O270 /O271 /O272 /O273 /O274 /O275 /O276 /O277 /O278 /O279 /O280 /O281 /O282 /O283 /O284 /O285 /O286 /O287 /O288 /O289 /O290 /O291 /O292 /O293 /O294 /O295 /O296 /O297 /O298 /O299 /O300 /O301 /O302 /O303 /O304 /O305 /O306 /O307 /O308 /O309 /O310 /O311 /O312 /O313 /O314 /O315 /O316 /O317 /O318 /O319 /O320 /O321 /O322 /O323 /O324 /O325 /O326 /O327 /O328 /O329 /O330 /O331 /O332 /O333 /O334 /O335 /O336 /O337 /O338 /O339 /O340 /O341 /O342 /O343 /O344 /O345 /O346 /O347 /O348 /O349 /O350 /O351 /O352 /O353 /O354 /O355 /O356 /O357 /O358 /O359 /O360 /O361 /O362 /O363 /O364 /O365 /O366 /O367 /O368 /O369 /O370 /O371 /O372 /O373 /O374 /O375 /O376 /O377 /O378 /O379 /O380 /O381 /O382 /O383 /O384 /O385 /O386 /O387 /O388 /O389 /O390 /O391 /O392 /O393 /O394 /O395 /O396 /O397 /O398 /O399 /O400 /O401 /O402 /O403 /O404 /O405 /O406 /O407 /O408 /O409 /O410 /O411 /O412 /O413 /O414 /O415 /O416 /O417 /O418 /O419 /O420 /O421 /O422 /O423 /O424 /O425 /O426 /O427 /O428 /O429 /O430 /O431 /O432 /O433 /O434 /O435 /O436 /O437 /O438 /O439 /O440 /O441 /O442 /O443 /O444 /O445 /O446 /O447 /O448 /O449 /O450 /O451 /O452 /O453 /O454 /O455 /O456 /O457 /O458 /O459 /O460 /O461 /O462 /O463 /O464 /O465 /O466 /O467 /O468 /O469 /O470 /O471 /O472 /O473 /O474 /O475 /O476 /O477 /O478 /O479 /O480 /O481 /O482 /O483 /O484 /O485 /O486 /O487 /O488 /O489 /O490 /O491 /O492 /O493 /O494 /O495 /O496 /O497 /O498 /O499 /O500 /O501 /O502 /O503 /O504 /O505 /O506 /O507 /O508 /O509 /O510 /O511 /O512 /O513 /O514 /O515 /O516 /O517 /O518 /O519 /O520 /O521 /O522 /O523 /O524 /O525 /O526 /O527 /O528 /O529 /O530 /O531 /O532 /O533 /O534 /O535 /O536 /O537 /O538 /O539 /O540 /O541 /O542 /O543 /O544 /O545 /O546 /O547 /O548 /O549 /O550 /O551 /O552 /O553 /O554 /O555 /O556 /O557 /O558 /O559 /O560 /O561 /O562 /O563 /O564 /O565 /O566 /O567 /O568 /O569 /O570 /O571 /O572 /O573 /O574 /O575 /O576 /O577 /O578 /O579 /O580 /O581 /O582 /O583 /O584 /O585 /O586 /O587 /O588 /O589 /O590 /O591 /O592 /O593 /O594 /O595 /O596 /O597 /O598 /O599 /O600 /O601 /O602 /O603 /O604 /O605 /O606 /O607 /O608 /O609 /O610 /O611 /O612 /O613 /O614 /O615 /O616 /O617 /O618 /O619 /O620 /O621 /O622 /O623 /O624 /O625 /O626 /O627 /O628 /O629 /O630 /O631 /O632 /O633 /O634 /O635 /O636 /O637 /O638 /O639 /O640 /O641 /O642 /O643 /O644 /O645 /O646 /O647 /O648 /O649 /O650 /O651 /O652 /O653 /O654 /O655 /O656 /O657 /O658 /O659 /O660 /O661 /O662 /O663 /O664 /O665 /O666 /O667 /O668 /O669 /O670 /O671 /O672 /O673 /O674 /O675 /O676 /O677 /O678 /O679 /O680 /O681 /O682 /O683 /O684 /O685 /O686 /O687 /O688 /O689 /O690 /O691 /O692 /O693 /O
```


[illegible]

[illegible]

-55-

[illegible]

[illegible]


```
// =====
void ColView::ColView(int type)
{
    ColDoc* pdoc = GetDocument();
    switch (type)
    {
        case SIGNED_VIEW, SIGNED_VIEW:
            // Set the window title.
            GetParent() ->SetWindowText(GetDocument() ->GetTitle() + " - Signed");
            break;
        case REF_VIEW:
            // Set the window title.
            GetParent() ->SetWindowText(GetDocument() ->GetTitle() + " - Reference");
            break;
        case ALIGNED_VIEW:
            // Set the window title.
            GetParent() ->SetWindowText(GetDocument() ->GetTitle() + " - Aligned");
            break;
        case STATUS_VIEW:
            m_viewType = STATUS_VIEW;
            // Set the window title.
            GetParent() ->SetWindowText(GetDocument() ->GetTitle() + " - Status");
            break;
        default:
            // This is an error.
            // Show message
            break;
    }
}

// =====
DisplayStatus()
{
    void ColView::DisplayStatus(CDC *pdc)
    {
        ColDoc* pdoc = GetDocument();
        TEXTMETRIC tm;
        CRect rect;
        CTIME t;
        pdc->GetMetrics(&tm);
        int col = 1000;
        int row = 1000;
        int width = 1000;
        int height = 1000;
        CreateStatusWindow(WS_CHILD | WS_VISIBLE | WS_VSCROLL, "", this, GetParent());
        int Height;
        rect.left = 0;
        rect.top = 0;
        rect.right = 100;
        rect.bottom = 100;
        Height = pdc->GetTextExtent(TEXT("A"), rect).height;
        rect.bottom = Height * 10;
        pdc->GetTextExtent(TEXT("A"), rect);
        // Resize the scrollbar to fit the information it contains.
        CSize size = CSize(rect.right-10, rect.bottom);
        ScrollBarCtrl sb(size);
        if (m_documentStatus == FALSE)
        {
            m_documentStatus = TRUE;
            Invalidate();
        }
        // Once we call _setC(), we must delete the allocated space.
        Delete m_cstr();
        return;
    }
}

// =====
CreateStatusWindow()
{
    void ColView::CreateStatusWindow()
    {
        ColDoc* pdoc = GetDocument();
        m_viewType = SIGNED_VIEW;
        // Set the window title.
        GetParent() ->SetWindowText(GetDocument() ->GetTitle() + " - Signed");
        pdoc->UpdateAllViews(NULL);
    }
}

// =====
OnViewAssigned()
{
    void ColView::OnViewAssigned()
    {
        ColDoc* pdoc = GetDocument();
        m_viewType = ORIGINAL_VIEW;
        // Set the window title.
        GetParent() ->SetWindowText(GetDocument() ->GetTitle() + " - Original");
        pdoc->UpdateAllViews(NULL);
    }
}

// =====
OnViewAssigned()
{
    void ColView::OnViewAssigned()
    {
        ColDoc* pdoc = GetDocument();
        m_viewType = ENCRYPT_VIEW;
        // Set the window title.
        GetParent() ->SetWindowText(GetDocument() ->GetTitle() + " - Code Pattern");
        pdoc->UpdateAllViews(NULL);
    }
}

// =====
OnViewAssigned()
{
    void ColView::OnViewAssigned()
    {
        ColDoc* pdoc = GetDocument();
        m_viewType = STATUS_VIEW;
        // Set the window title.
        GetParent() ->SetWindowText(GetDocument() ->GetTitle() + " - Status");
        pdoc->UpdateAllViews(NULL);
    }
}

```


[illegible]

[illegible]